

POWER INVERTOR (BLUE)



Features:

Thermal Protection

- The unit shut down when it overheats

Battery alarm

- Alarm activated when battery discharges to 10.6 V

Battery Protection

- The unit shutdown when battery discharges to 10V (prevent damage to battery)

Overload Protection

- The unit shutdown when the loading power exceeds the rating power

Short Circuit Protection

- The unit shutdown when output is short circuit

Earth fault Protection

- The unit shutdown when the load has electric leakage



TECHNICAL SPECIFICATIONS

	Rated input voltage	12VDC (Auto)	24 VDC (Auto)
	INPUT	The range of rated input voltage	10.0~15.5 VDC
Input overvoltage or undervoltage		Output shutoff, voltage recovering, inverter auto-launch	
Overload, short circuit		Output shutoff, restart using / inverter auto-launch when fault disappears	
Overheating		Output shutoff, restart using / inverter auto-launch when fault disappears	
Input polarity reversal		Blown fuse	
ENVIRONMENT		Working temperature	-10 °C ~ 40 °C
	Working humidity	-20 % ~ 90% RH non-condensational	
	Store Temperature and humidity	-20 °C ~ 55 °C / 10 °C ~ 95 % RH	
	Working height	The height can not be over 1000m, or using as Gb/T3859.2 derating.	
	Refrigeration	Cooling fans are controlled by the load	
	Adhibition	Small medol off grid system, wind energy supply system, electric tools. Vehicle mounted, ships and some other portable power source	

MODEL	500 W	1000 W	2000 W	3000 W	5000 W	
Rated output voltage	500 W	1000 W	2000 W	3000 W	5000 W	
Peak Power	1000 W	2000 W	4000 W	6000 W	10000 W	
Packaging Size	Length	22 cm	26 cm	32 cm	37 cm	44 cm
	Width	14.5 cm	19.5 cm	24 cm	24 cm	26 cm
	Height	6 cm	7.5 cm	13 cm	13 cm	15 cm



UNDER VOLTAGE PROTECTION



OVER VOLTAGE PROTECTION



SHORT CIRCUIT PROTECTION



OVER HEATING PROTECTION



OVER LOAD PROTECTION